



Seasoned slaked lime based finish for interior and exterior wall surfaces

RIALTO EPOCA MARMO replicates the smooth marmorino look of the ancient lime plasters. A matte or shiny effect can be achieved with a chrome trowel. Depending on color and application, mottling will vary. **EPOCA MARMO** is made up of seasoned slaked lime rich of magnesium, selected white fine Carrara marbles, natural earths, inorganic pigments and mineral additives. The aggregate is finer than **RIALTO ANTIQUA I** but coarser than **RIALTO EPOCA SPATOLATO**. **EPOCA MARMO** is a light weight lime plaster that can be applied over **RIALTO FINISH (PRIMER)** and **RIALTO ANTIQUA**.

PROPERTIES

- ready-to-use
- allows surfaces to breathe:
410 g/m² - 24h (DIN 53122 regulations),
 $\mu=50$, $Sd=0.4$ m
- marine air resistant (400 hours
exposure – ASTM-B 117)
- withstands with alkali corrosion
- not prone to shrinkage
- abrasion resistant
- non-flammable
- does not flake or peel
- specific gravity: 1.65 ± 0.05 kg/l
- pH: 13.5 ± 0.5
- viscosity at quality control:
non-Newtonian product average
value $> 36.00 \pm 2.00$ mPas
- dry residue: $70 \pm 2\%$ by weight
- VOC: 15 g/l (including pigment)

PURPOSES

RIALTO EPOCA MARMO is ideal for giving interior and exterior surfaces a natural decorative effect with a very smooth marmorino appearance. The high quality of its natural components make this plaster product good for use in kitchens, bathrooms, and contemporary exteriors for a smooth even look.

Provided that surfaces are sound and clean **RIALTO EPOCA MARMO** is suitable for the following applications:

- over surfaces prepared with **RIALTO FINISH**
- **RIALTO ANTIQUA**

Rios Plastering Location: Scottsdale, AZ



V-1083 x2

WORKING INSTRUCTIONS

- when applying to plaster which is old or covered with traces of old paint or to new plaster with cracks that have been filled in, remove loose material and dampen all the surface with water before smoothing it down with **RIALTO FINISH** and let it dry for 24 hours before application of **RIALTO EPOCA MARMO**
- apply **RIALTO FINISH** first before applying **RIALTO EPOCA MARMO**. Let dry at least 24 hours
- apply **RIALTO EPOCA MARMO** with stainless chrome trowel in two coats and polish with same tool, allow 24 hours before applying next coat
- protect the newly applied coat from heavy rain for about 48 hours for exterior use
- do not apply at air surface temperature below 5°C (41°F) or exceeding 30°C (86°F) and to overheated surfaces
- store the product at a temperature above 5°C (41°F) and below 30°C (86°F)
- check with your local department of environmental quality for disposal requirements and recycle whenever possible

COVERING CAPACITY

The average coverage of **RIALTO EPOCA MARMO** is 100 sq. ft. per pail per coat first coat and 50 sq. ft. per pail two coats.

PACKAGING

RIALTO EPOCA MARMO is available in 10 kg/22 lb. containers.

COLOR RANGE

RIALTO EPOCA MARMO is available in a wide range of colors (see Collezione Italia fandeck). We also offer over 400 standard colors, or we will gladly customize your color match.

REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

RIALTO FINISH
RIALTO ANTIQUA
RIALTO SOLUTION
RIALTO CERA D'ARTE

VERO

2911 North Orange-Olive Road
Orange, CA 92865
714.637.7341
714.637.7364 Fax
www.vero-rialto.com



Environmental Partnership:

Our products were manufactured in an environmentally compatible manner. Vero reminds you to properly handle and dispose of all materials in accordance with regulations established in your area. Caring for our environment is best achieved when we do it together.