



## Seasoned slaked lime based finish for interior and exterior wall surfaces

**RIALTO EPOCA SPATOLATO** has a smooth glossy spatula effect. It is made up of seasoned slaked lime, natural pigments, and selected mineral additives.

### PROPERTIES

- ready-to-use
- allows surfaces to breathe:  
430 g/min<sup>2</sup> 24 hours  
(DIN 53122 Regulations),  
 $\mu=80$ ,  $Sd=0.05$  m
- withstands alkali corrosion
- not prone to shrinkage
- abrasion resistant
- non-flammable
- does not flake or peel
- specific gravity:  
1.60 ± 0.05 kg/l
- pH: 13.5 ± 0.5
- dry residue: 66 ± 1% by weight
- VOC: 20 g/l (including pigment)

### PURPOSES

**RIALTO EPOCA SPATOLATO** is widely used in conservation work on projects located in Italian historical cities. **RIALTO EPOCA SPATOLATO** is ideal for use on exterior masonry surfaces to achieve a decorative, "old world" effect. **RIALTO EPOCA SPATOLATO** can also be applied on interior walls.

Provided that surfaces are sound and clean, **RIALTO EPOCA SPATOLATO** is suitable over the following surfaces:

- **RIALTO ANTIQUA**
- **RIALTO NLP**
- over surfaces prepared with **RIALTO FINISH**

*Thom Susko Construction Location: Anaheim Hills, California*



**V-430 EPOCA SPATOLATO over ANTIQUA I**

## WORKING INSTRUCTIONS

- on new and smooth plaster interiors, apply **RIALTO FINISH** directly using a roller or sprayer and let dry for **24 hours** before applying **RIALTO EPOCA SPATOLATO**
- on old plaster remove any loose material, apply a level coat of plaster and apply a coat of **RIALTO FINISH**. Allow at least **24 hours** for surface to dry before applying **RIALTO EPOCA SPATOLATO**. Apply first coat of **RIALTO EPOCA SPATOLATO** using a chrome spatula
- when applying **RIALTO EPOCA SPATOLATO** over **RIALTO ANTIQUA**, apply 1-2 coats of **RIALTO ANTIQUA**. Allow to dry **24 hours** before applying 2 coats of **RIALTO EPOCA SPATOLATO**
- apply a total of three coats. Allow **24 hour** intervals between each coat
- Protect from rain for at least **48 hours**
- do not apply **RIALTO EPOCA SPATOLATO** when temperatures are below 46°F (8°C)
- store product in a sealed container in a dry place at temperatures higher than 41°F (5°C) and lower than 86°F (30°C)
- check with your local department of environmental quality for disposal requirements and recycle whenever possible

Tom Crow Plastering Location: San Clemente, California



V-137

## COVERING CAPACITY

When the product is applied with a trowel or sponge float, the average covering capacity is 400 sq. ft. per pail, per coat.

## PACKAGING

**RIALTO EPOCA SPATOLATO** is available in 10 kg/22 lb. containers.

## COLOR RANGE

**RIALTO EPOCA SPATOLATO** is available in 24 standard colors, 400 fandeck colors, or we can match any custom color.

## REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

**RIALTO FINISH**  
**RIALTO ANTIQUA**  
**RIALTO CERA D'ARTE**  
**RIALTO NLP**

## VERO

2911 North Orange-Olive Road  
Orange, CA 92865  
714.637.7341  
714.637.7364 Fax  
www.vero-rialto.com



### Environmental Partnership:

*Our products were manufactured in an environmentally compatible manner. Vero reminds you to properly handle and dispose of all materials in accordance with regulations established in your area. Caring for our environment is best achieved when we do it together.*