



## Seasoned slaked lime based paint for interior and exterior wall surfaces

**RIALTO EPOCA OTTOCENTO** has a brushed matte or a glazed decorative appearance. It is composed of seasoned slaked lime, natural earth, inorganic oxides, and mineral additives.

### PROPERTIES

- allows surfaces to breathe  
430 g/m<sup>2</sup>-24h (DIN 53122 Regulations),  
 $\mu=140$ , Sd=0.05 m
- good adhesion
- withstands alkali corrosion
- highly abrasion resistant
- non-flammable
- does not flake or peel
- specific gravity: 1.38 ± 0.03 kg/l
- pH: 13-13.5
- dry residue: 54 ± 0.1% by weight
- VOC: 7 g/l (including pigment)

### PURPOSES

**RIALTO EPOCA OTTOCENTO** is ideal for use on exterior masonry surfaces to achieve an "old-lime" watercolor effect, and can also be used on interior surfaces.

**RIALTO EPOCA OTTOCENTO** is widely used especially in carrying out historic restoration work, and can be used as a paint or as a plaster.

Provided surfaces are sound and clean, **RIALTO EPOCA OTTOCENTO** coating can be applied to:

- **RIALTO ANTIQUA**
- **RIALTO NLP**
- surfaces prepared with **RIALTO FINISH**
- clean brick
- stone
- smooth cementitious stucco

*Special T Painting Location: The Resort at Pelican Hill: Newport Coast, CA*



## WORKING INSTRUCTIONS

- on patched plaster or surfaces with damaged old paint, remove old paint, level off entire surface, apply 1 coat of **RIALTO FINISH** and allow at least **24 hours** before starting the finishing treatment
- on old plaster remove any loose material, apply a level coat of plaster and apply a coat of **RIALTO FINISH**. Allow at least **24 hours** for surface to dry before applying **RIALTO EPOCA OTTOCENTO**.
- stir thoroughly before use, making sure the product is well mixed; if no, use a mechanical mixer
- for a painted application, apply using a brush, diluting the product to not more than 15% with water
- for a troweled appearance, use a chrome-plated trowel and apply in thin coats
- if sealing **RIALTO EPOCA OTTOCENTO**, use **RIALTO VELASIL** on exteriors, and either **RIALTO VELASIL** or **RIALTO CERA D'ARTE** on interiors
- allow **24 hours** before applying next coat
- do not apply in rainy weather, when temperatures are below 46°F (8°C) and never on surfaces either frozen or overheated by the sun
- protect applied coat from rain for approximately **48 hours**
- store product at temperatures not lower than 41°F (5°C) or above 86°F (30°C)
- check with your local department of environmental quality for disposal requirements and recycle whenever possible

## COVERING CAPACITY

Covering capacity is approximately 600-800 sq. ft. (two coats), but will vary depending on substrate

## PACKAGING

**RIALTO EPOCA OTTOCENTO** is available in 3.9 gal containers.

## COLOR RANGE

**RIALTO EPOCA OTTOCENTO** is available in 24 standard colors, 400 fandeck colors, or we can match any custom color.

## REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

**RIALTO FINISH**

**RIALTO ANTIQUA**

**RIALTO CERA D'ARTE**

**RIALTO VELASIL**

## VERO

2911 North Orange-Olive Road  
Orange, CA 92865  
714.637.7341  
714.637.4865 Fax  
www.vero-rialto.com



rialto@rialto-colors.com  
www.rialto-colors.com