

Natural Lime Plaster

RIALTO NLP is a natural slaked lime plaster, suitable for interiors and exteriors.

PROPERTIES

- allows surfaces to breathe (380 g/m² - 24 h DIN 53122)
- strong adhesion to properly treated wall surfaces
- ocean air resistant (500 hours exposure, ASTM B 117)
- withstands alkali corrosion
- not prone to shrinkage
- abrasion resistant
- non-flammable
- does not flake or peel
- specific gravity: 1.7 kg/l
- pH: 13 – 13.5
- VOC: 8.5 g/l (including pigment)

PURPOSES

Provided the surfaces are sound and dry, **RIALTO NLP** can be applied to the following surfaces:

- surfaces prepared with **RIALTO FINISH**

WORKING INSTRUCTIONS

- when applying to plaster which is old or covered with traces of paint or even to new plaster with cracks or ones that have been filled in, remove loose material, apply a level plaster coat and prime with
- wait at least before applying
- apply with chrome trowel and finish off with wet sponge float or chrome trowel when it starts to set.
- protect the newly applied coat from rain for about
- do not apply at air surface temperature below 50°F (10°C) or exceeding 95°F (35°C) and to overheated surfaces.
- store the product at a temperature of above 41°F (5°C) and not exceeding 86°F (30°C).
- check with your local department of environmental quality for disposal requirements and recycle whenever possible.

The Roger Miller Company Location: HBO Office, Santa Monica, California



V-668

COVERING CAPACITY

- approx. 150-200 sq. ft. one coat and approx. 80-100 sq. ft. two coats applied to fine plaster.

PACKAGING

RIALTO NLP is available in 25 kg/55 lb. containers.

COLOR RANGE

RIALTO NLP is available in white, over 400 fandeck colors, or we can match any custom color.

REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

RIALTO FINISH

VERO

2911 North Orange-Olive Road
Orange, CA 92865
714.637.7341
714.637.7364 Fax
www.vero-rialto.com



Environmental Partnership:

Our products were manufactured in an environmentally compatible manner. Vero reminds you to properly handle and dispose of all materials in accordance with regulations established in your area. Caring for our environment is best achieved when we do it together.

COVERING CAPACITY

- approx. 150-200 sq. ft. one coat and approx. 80-100 sq. ft. two coats applied to fine plaster.

PACKAGING

RIALTO NLP is available in 25 kg/ 55 lb. containers.

COLOR RANGE

RIALTO NLP is available in white, over 400 fandeck colors, or we can match any custom color.

REFERENCES

For further information regarding the product mentioned in the text, see the following technical sheets:

RIALTO FINISH

VERO

2911 North Orange-Olive Road
Orange, CA 92865
714.637.7341
714.637.7364 Fax
www.vero-rialto.com



Environmental Partnership:

Our products were manufactured in an environmentally compatible manner. Vero reminds you to properly handle and dispose of all materials in accordance with regulations established in your area. Caring for our environment is best achieved when we do it together.